



Stock No. 105011

# Humax PVR-8000T

## Personal Video Recorder

- Quick Setup (Plug-n-Play Installation)
- MPEG2 Digital & Fully DVB-T Compliant
- 200 Channel storage
- 5 Favourite groups
- Subtitle supports EBU & DVB subtitle
- Teletext supports by VBI insertion
- Dolby Digital Audio Output
- Various Games
- Universal Remote Control Compatible with most TV's

System Resource	
CPU	STi5518
Flash	4MB
SDRAM	24MB
EEPROM	8KB
HDD Storage	80GB
Power Supply	
Input Voltage	AC 90-250, 50/60Hz
Type	Switching Mode Power Supply
Power Consumption	Max. 30W (without HDD) Standby: Max. 8W
Protection	Separate internal fuse & Lightning protection
Demodulator	
Waveform	OFDM
Mode	2K, 8K
Codes Rates	1/2, 2/3, 3/4, 5/6, 7/8
Guard Intervals	1/4, 1/8, 1/16 & 1/32
Tuner & Channel	
1 Input Connector	IEC 169-2, Female
Frequency Range	48.5MHz~226.5MHz(VHF) 470MHz~862MHz (UHF) -10~-70 dBm
Video Decoder	
Transport stream	MPEG2 ISO / IEC 13818
Profile Level	MPEG2 MP@ML
Input Rate	Max. 15 Mbit/s
Video Formats	4:3, 16:9 Letterbox (Default)
Video Output	CVBS (Default), RGB, S-Video
Video Resolution	Max. 720 x 576
Audio Decoder	
Audio Decoding	MPEG/MusiCam Layer I & II
Audio Mode	Single/Dual Mono/Stereo /Joint stereo

RF-Modulator	
RF Output Connector (Loop throughout)	75Ω, IEC 169-2, Male
Frequency	470 MHz ~ 862 MHz
Output Channel	CH21-69 for Modulator
TV Standard	PAL B/G/I selectable by menu
SCART	
TV SCART	Video Output (CVBS, RGB, S-Video) Audio Output (Max. 2 Vrms)
VCR SCART	Video Input (CVBS, RGB, S-Video) Video Output (CVBS, S-Video) Audio Output (Max.2 Vrms)
RCA	
Video RCA	1 Output
Audio RCA	2 Output (Left, Right)
Data Port	
RS-232C	3-pin
Front	
Buttons	10 Keys (Standby/On, TV/Radio, MENU, GUIDE, EXIT, OK/CH. List, Arrow keys)
Indicators	1 LEDs (Standby/On)
Display	4 digit 7-segment
Rear	
Main Power cable	Fixed Type
Tuner	1 Antenna Input
SCARTs	1 for TV, 1 for VCR
RCA	1 Video Output 2 Audio Output (Left & Right)
Data Port	1 RS-232C (3 pin type)
Power Switch	Yes
RF Modulator	1 Output
S/PDIF	1 Output
Physical Specification	
Size (WxHxD)	370x60x262
Weight (net)	2.7kg without HDD
Operating Temperature	0°C~+45°C
Storage Temperature	-10°C ~ +70°C
Accessories	
	Universal RCU, User's Manual, 2 Batteries (AAA), Scart Cable

PVR

Phone: 08 9409 6677 Fax: 08 9309 5210

Web: [www.sciteq.com.au](http://www.sciteq.com.au)

Email: [sales@sciteq.com.au](mailto:sales@sciteq.com.au)

**SCITEQ**